



ENIGMAHYO

An advanced multipoint correlation system for locating leaks in buried pipes of any material over long distances

ENIGMA LOGGER

Sensor

Type	Hydrophone (connected externally)
Sensitivity	-195dB
Frequency range	1- 2400 Hz
Attachment	1" BSP connection + pipe adaptors

Sampling

Rate	4860 Hz
Resolution	24-bit
Number of epochs	1, 2, or 3
Epoch duration	60 seconds
Max total recording time	180 seconds

Memory

Data store	32MB static RAM
------------	-----------------

Communications

Type	Optical
Rate	2.5 Mbits/sec

Power Supply

Type	Dual lithium cells
Replaceable	At factory or service centre
Operating life	>5 years (when standard programming used)

Physical

Dimensions	104mm (high) x 59mm (diameter)
Material	Aluminium
Waterproof rating	Submersible to IP68
Operating Temperature	-10 to +60 deg C

COMMUNICATIONS CASE

PC Comms

Type	USB
Rate	2.5 Mbits/sec
Data saved into case	One run (8 correlations)

Power Supply

Type	User replaceable alkaline 4 cell pack
------	---------------------------------------

Physical

Dimensions (logger case)	8 logger: 410 x 325 x 172 mm 3 logger: 270 x 246 x 174 mm
Material	Ruggedised high impact plastic
Waterproof rating	IP65
Operating Temperature	-10°C to +60°C

www.ovarro.com

Ovarro has a global network of offices and distributors. Visit our website to find your local office.

