



## (PRIMEPROBE

Bi-directional, insertion, electromagnetic flowmeter for permanent or portable use

Pipe sizes 80mm to >2000mm. Maximum size dependant on position in pipe (for pipe sizes ≤150mm

accuracy can be improved by special calibration at the specified pipe size).

Measurement range Bi-directional from 0.02m/s to 5m/sec (maximum may be lower dependent upon insertion length

and position in pipe)

**Accuracy** Point velocity ≥0.4m/s; ±2%

(See Note 1 below) Point velocity < 0.4m/s; ±0.8/V% (V = measured water velocity)

Flow determination Assumes developed profile (determine via Flow Profiling Software)

Response time Liquid speed step variations >0.25m/s; Liquid speed step variations <=0.25m/s;

 Continuous mode
 300ms
 6s

 SMART mode
 3s
 60s

 Average mode
 6s
 120s

 Maximum life mode
 15s
 300s

Minimum fluid conductivity 20µS/cm

**Process connection** 1 inch (25mm) BSP threaded end

Pipeline Pressure rating 25 Bar Sensor material Peek

Body/electrodes material Stainless steel AISI 316

Liquid temperature range 0°C to 60°C

Safety Probe fitted with safety/anti-bounce chain

Pressure tapping Female quick-release connector
Adjustment method 5mm Allen key (supplied) fits all screws

**Protection** IP68 (to 1 metre depth)

Battery type 2 x Lithium cells size D (non-rechargeable)

**Battery life** 

Continuous mode 7.8 months
SMART mode 4.8 years
Average mode >8 years
Maximum life mode >10 years

Output signal Pulses proportional to velocity/flow-rate (max. frequency 100 Hz)

**Communications** USB

Materials certification WRAS drinking water material Approval Number 1205543

ACS Approval Number 16ACC LY 116

## **DIMENSIONS IN DETAIL**

Nominal probe size	150mm	300mm	500mm	700mm	1000mm	2000mm
Internal ref	0	1	2	3	4	5
Ref	RXG731	RXG732	RXG733	RXG734	RXG735	RXG736
Height of transmitter w/o connector	96mm	96mm	96mm	96mm	96mm	96mm
Height of connector below transmitter	25mm	25mm	25mm	25mm	25mm	25mm
Height of adjustable indicator	20mm	20mm	20mm	20mm	20mm	20mm
Distance of electrodes from tip	30mm	30mm	30mm	30mm	30mm	30mm
Mounting collar BSP/NPT	108mm	108mm	108mm	108mm	108mm	108mm
Maximum insertion length	359mm	509mm	709mm	909mm	1209mm	2209mm
Total length	638mm	788mm	988mm	1188mm	1488mm	2488mm

Note 1; Reference conditions:

- a) Constant flow rate during the test
- b) Pressure: >30 kPa
- c) Flow condition : fully developed flow profile
- d) Zero stability +/- 0,005 %
- e) Pipe internal diameter accuracy: mean value better than 1%

